



General Authority of Civil Aviation

Syrian Arab Republic — Electronic Aeronautical Information Publication

ENR 1.4

ENR

CATEGORY	EFFECTIVE DATE	AMENDMENT	STATUS
ENR	27 Mar 2026	AMDT 01/2026	Published

ATS Airspace Classification and Description

ةيوجل ةكرحل ءامءخ ءالءم فءووفينء

ENR 1.4 ATS AIRSPACE CLASSIFICATION AND DESCRIPTION

1. General

ICAO has indicated that States are required to select the classes of ATS airspace that best fit their needs. The following classes have been selected for application within Damascus FIR:

- CLASS A** — Replaces "instrument restricted airspace". Includes all controlled airspace at FL150 and above.
- CLASS B** — Replaces "visual exempted airspace". Includes all controlled airspace below FL150.

Classifications of other airspace are undefined because they are not used by civil aircraft.

2. REQUIREMENTS FOR FLIGHTS

The requirements for flights within each class of airspace are as shown in the table on pages ENR 1.4-2 and ENR 1.4-3.

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
A	IFR only	All aircraft	Air traffic control service	Not applicable	Not applicable	Continuous two-way	Yes
B(3)	IFR	All aircraft	Air traffic control service	Not applicable	Not applicable	Continuous two-way	Yes
	VFR	All aircraft	Air traffic control service	8 KM at and above 3050 M (10000 FT) AMSL 5 KM below 3050 M (10000 FT) AMSL Clear of clouds	Not applicable	Continuous two-way	Yes

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
C	IFR	IFR from IFR IFR from VFR	Air traffic control service	Not applicable	250 KT IAS below 3050 M (10000 FT) AMSL, unless advised by ATC.	Continuous two-way	Yes
	VFR	VFR from IFR	1) Air traffic control service for separation from IFR; 2) VFR/VFR traffic information (and traffic avoidance advice on request)	8 KM at and above 3050 M (10000 FT) AMSL 5 KM below 3050 M (10000 FT) AMSL 1500 M horizontal; 300 M vertical distance from cloud	250 KT IAS below 3050 M (10000 FT) AMSL	Continuous two-way	Yes

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
D	IFR	IFR from IFR	Air traffic control service including traffic information about VFR flights (and traffic avoidance advice on request)	Not applicable	250 KT IAS below 3050 M (10000 FT) AMSL	Continuous two-way	Yes

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
VFR	Nil	Traffic information between VFR and IFR flights (and traffic avoidance advice on request)	8 KM at and above 3050 M (10000 FT) AMSL 5 KM below 3050 M (10000 FT) AMSL 1500 M horizontal; 300 M vertical \ distance from cloud	250 KT IAS below 3050 M (10000 FT) AMSL	Continuous two-way	Yes	
E(3)	IFR	IFR from IFR	Air traffic control service and traffic information about VFR flights as far as practical	Not applicable	250 KT IAS below 3050 M (10000 FT) AMSL	Continuous two-way	Yes

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
VFR	Nil	Traffic information as far as practical	8 KM at and above 3050 M (10000 FT) AMSL 5 KM below 3050 M (10000 FT) AMSL 1500 M horizontal; 300 M vertical distance from cloud	250 KT IAS below 3050 M (10000 FT) AMSL	No	No	
F(3)	IFR	IFR from IFR as far as practical	Air traffic advisory service; flight information service, radar advisory service.	Not applicable	250 KT IAS below 3050 M (10000 FT) AMSL	Continuous two-way	No

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
VFR	Nil	Flight information service, radar advisory service.	8 KM at and above 3050 M (10000 FT) AMSL 5 KM below 3050 M (10000 FT) AMSL 1500 M horizontal; 300 M vertical distance from cloud. At and below 900 M AMSL or 300 M above terrain whichever is higher - 5 KM, clear of cloud and in sight of ground or water	250 KT IAS below 3050 M (10000 FT) AMSL	No	No	

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
G	IFR	Nil	Flight information service	Not applicable	250 KT IAS below 3050 M (10000 FT) AMSL	Continuous two-way	No

CLASS	TYPE OF FLIGHT	SEPARATION PROVIDED	SERVICE PROVIDED	VMC VISIBILITY AND DISTANCE FROM CLOUD MINIMA	SPEED LIMITATION	RADIO COMMUNICATION REQUIREMENT	ATC CLEARANCE
VFR	Nil	Flight information service	8 KM at and above 3050 M (10000 FT) AMSL 5 KM below 3050 M (10000 FT) AMSL 1500 M horizontal; 300 M vertical distance from cloud. At and below 900 M AMSL or 300 M above terrain whichever is higher - 5 KM (1), clear of cloud and in sight of ground or water	250 KT IAS below 3050 M (10000 FT) AMSL(2)	No (Except continuous two-way required when operating in Class G at an aerodrome with ATS)	No	

1) When so prescribed by the appropriate ATS authority:

(a) Lower flight visibilities to 1500 M may be permitted for flights operating:

1) at speeds that will give adequate opportunity to observe other traffic or any obstacles in time to avoid collision; or

2) in circumstances in which the probability of encounters with other traffic would normally be low, e.g., in areas of low traffic volume and for aerial work at low levels;

b) Helicopters may be permitted to operate in less than 1500 M flight visibility, if maneuvered at a speed that will give adequate opportunity to observe other traffic or any obstacles in time to avoid collision.

Amendment History

AMENDMENT NO.	CHANGE SUMMARY	EFFECTIVE DATE
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026
AMDT 01/2026	Content updated	27 Mar 2026

This document is published by the Syrian General Authority of Civil Aviation for aeronautical information purposes. Verify the current effective date before operational use. Consult active NOTAMs for supplements and temporary amendments.

DIGITAL VERIFICATION CERTIFICATE

This document was digitally signed by the GACA eAIP System.
To verify authenticity, visit the URL below or scan the verification code.

**GACA-SECTION-ENR 1.4-20260605-233023-
E2F49C866A0C065F**

Generated: 2026-06-05T23:30:23 | Type: SECTION

HMAC-SHA256 SECURED | GENERAL CIVIL AVIATION AUTHORITY (GACA) | SYRIAN ARAB REPUBLIC

VERIFY AT

<https://www.eaip.gaca.gov.sy/verify>

AUTHENTICATED